

2100VA/1800W Backup Battery (UPS)



- Line-interactive UPS Topology
- Generator Compatible
- EMI and RFI Filtration
- Configurable Alarm
- Automatic Voltage Regulation (AVR)
- Overload Protection

Specifications

UPS	
Model	OLS1500SE
Capacity (VA)	2100VA
Capacity (Watts)	1800W
Form Factor	Tower
Phase	Single Phase
INPUT	
Generator Compatibility	YES
Nominal Input Voltage (Vac)	230 ± 10%
Input Voltage Range (Vac)	165 ~ 290
Input Frequency (Hz)	50 ± 10 60 ± 10
Input Frequency Detection	Auto-sensing
Rated Input Current (A)	6.82
Power Cord Length (m.)	1.2
OUTPUT	
Waveform	Simulated Sine Wave
On Battery Voltage(s) (Vac)	230 ± 10 %
On Battery Frequency (Hz)	50 ± 1% 60 ± 1%
Automatic Voltage Regulation (AVR)	Single Boost, Single Buck
Overload Protection	Circuit Breaker

BATTERIES AND AUTONOMY	
Runtime at 60W (min)	90
Runtime at 90W (min)	60
Typical Recharge Time (Hours)	8
Start On Battery	YES
User-replaceable	No
Battery Type	Sealed Lead-acid
COMMUNICATION	
LED Indicators	Power On, Line Mode, Battery Mode, Battery Capacity, Low Battery
HID Compliant USB Port(s)	1
Audible Alarms	Battery Mode, Low Battery, Overload, UPS Fault
Power Management Software	PowerPanel Personal (Recommended)
ENVIRONMENT	
Noise Level	< 45dB
Fan Logic	Always on, Automatic Speed Control
Temperature	0°C – 40°C
Humidity	0% - 90% RH (non-condensing)
PHYSICAL	
Dimensions (WxDxH)	148 x 298 x 178mm
Weights (kgs)	9.1

