

4 Port 100M AI POE Switch



- 4*10/100M POE ports + 2*10/100M Ethernet Uplink ports
- Comply with IEEE 802.3, IEEE 802.3u, IEEE802.3af/at standards
- Ethernet port supports 10/100M adaptive and POE functions
- Flow control mode: full-duplex adopts IEEE 802.3x standard
- Automatically supplied to adaptive devices

Specifications

Model	OTR426
I/O Interface	
Power	Input: AC 100-240V, 50/60Hz
Ethernet	4 Port 10/100M PoE + 2 Port 100M Ethernet Uplink
Performance	
Switching Capacity	1.2Gbps
Throughput	0.8928Mpps
Packet Buffer	448K
MAC Address	1K
Jumbo Frame	2Kbytes
Transfer Mode	Store and forward
MTBF	100000 hour
Standard	
Network protocol	IEEE802.3 (10Base-T) IEEE802.3u (100Base-TX) IEEE802.3x (Flow control)
PoE Protocol	IEEE802.3af (15.4W) IEEE802.3at (30W)
Industry Standard	EMI: FCC Part 15 CISPR (EN55032) class A EMS: EN61000-4-2 (ESD) EN61000-4-5 (Surge)
Network Medium	10Base-T: Cat 3, 4, 5 or above UTP(≤100m) 100Base-TX : Cat5 or above UTP(≤100m)
Protection	
Security Certificate	CE、FCC、RoHS
Environment	
Working Environment	Working Temperature : -10~50°C Storage Temperature : -40~70°C Working Humidity : 10%~90%, non-condensing

	Storage Temperature : 5%-90%, non-condensing
Indication	
LED Indicators	PWR (power supply) , SW (DIP) , 1-10 Green (Link&Data)
DIP Switch	VLAN : Port isolation mode. In this mode, the PoE ports (1-4) of the switch can not communicate with each other, and can only communicate with the UP-link port. The port AI mode is turned on. Normal: Normal mode, all port can communicate with each other, the transmission distance is within 100 meters, the transmission rate is 10M / 100Madaptive; The port AI mode is closed. Extend : Link extension mode, 1-4 ports PoE power supply and data transmission distance can be extended to 250 meters, the transmission rate becomes 10M, and the port AI mode is turned on
Mechanical	
Structure Size	Product Dimension : 200*118*44mm Package Dimension : 245*190*60mm N.W : 0.60kg G.W : 0.86kg
Packing Info	Carton MEAS : 520*320*400mm Packing Qty : 20 units Packing Weight : 18.2KG
Power Voltage	Input Voltage: AC 100-240V Power Supply: 52V1.25A
Package List	Switch 1 pcs, Power cord 1 pcs, User manual 1 pc, Certificate 1 pc

Product Picture

