

## 2MP(FHD) IR POE Network Dome Camera



- IR POE Dome Camera
- Fixed-focal (3.6mm)
- H.265/H.264
- 1920\*1080 Mainstream resolution
- Support body detection & human frame

### Specifications

Model	OTRAFG204WHD
<b>Camera</b>	
Image Sensor	1/3" 2MP CMOS Sensor
Resolution	2MP
Effective Pixels	1920(H)*1080(V)
Lens	3.6mm
Compression	H.265/H.264
LUX	Color 0.05Lux@F1.2; B&W 0.005Lux@F1.2
S/N	≥50db(AGC OFF)
WDR	DWDR: >80db
<b>Audio</b>	
Audio/Intercom Input	Audio MIC Input (optional)
Audio Output	Built-in power magnify circuit
LED Type	CDS IR / Sensor Control / Warm LED / Extra add LED drive board (Optional)
Other Function	IRCUT, Reset
Extension Function	Extension with IO
<b>Network</b>	
Main Stream	2560*1440, 1-25fps/s 2304*1296、1920*1080、1280*720,1-30fps/s
Sub Stream	704*576、640*480、640*360、352*288,1-30fps/s
Video Coding Compression	128Kbps-8192bps Continuous Adjustable
Subtitle Overlay	Support Channel Name & Data & Time & Frame & Resolution & 4 Lines of Character Overlay
<b>Data Transmission &amp; Storage</b>	
Data Record	Video & Picture
Storage Method	Cycling Recording & Alarm Recording
Alarm Transfer	Brower & Management Software, App
Protocol	ONVIF

Browser	Support IE Brower & Management Software Viewing
Mobile	WANAN App/IOS/Android
<b>Technical Specifications</b>	
Temperature	-30°C ~ +60°C
Humidity	0% - 90%
Power	DC12V/150mA
Dimensions	Φ 107 x 90(H) mm
Consumption	< 2W

## Dimensions

