

## 4MP(2K) IR IK10 IP67 POE Network Dome Camera



- IR POE Dome Camera
- Fixed-focal (2.8mm / 3.6mm)
- H.264/H.264+/H.265/H.265+
- 2688\*1522 Mainstream resolution
- IK10, IP67

### Specifications

| Model                                  | OTRAFG404WHDI  |
|--|--|
| <b>Camera</b>                          |  |
| Image Sensor                           | 1/3" Progressive CMOS  |
| Resolution                             | 4MP  |
| Effective Pixels                       | 2688(H)*1522(V)  |
| Lens                                   | 2.8mm / 3.6mm  |
| Compression                            | H.264/H.264+/H.265/H.265+  |
| LUX                                    | Color 0.05Lux@F1.2; B&W 0.005Lux@F1.2  |
| S/N                                    | ≥50db(AGC OFF)   |
| WDR                                    | 120 dB   |
| Illumination Distance                  | up to 30 m (98.43 ft) (IR LED)   |
| <b>Audio</b>                           |  |
| Audio/Intercom Input                   | Audio MIC Input (optional)   |
| Audio Output                           | Built-in power magnify circuit   |
| LED Type                               | CDS IR / Sensor Control / Warm LED / Extra add LED drive board (Optional)              |
| Other Function                         | IRCUT, Reset   |
| Extension Function                     | Extension with IO  |
| <b>Network</b>                         |  |
| Main Stream                            | 2560*1440, 1-25fps/s   |
|  | 2304*1296、1920*1080、1280*720,1-30fps/s   |
| Sub Stream                             | 704*576、640*480、640*360、352*288,1-30fps/s  |
| Video Coding Compression               | 128Kbps-8192bps Continuous Adjustable  |
| Subtitle Overlay                       | Support Channel Name & Data & Time & Frame & Resolution & 4 Lines of Character Overlay |
| <b>Data Transmission &amp; Storage</b> |  |
| Data Record                            | Video & Picture  |
| Storage Method                         | Cycling Recording & Alarm Recording  |
| Alarm Transfer                         | Brower & Management Software, App  |

|                                 |   |
|---------------------------------|---|
| Protocol                        | ONVIF   |
| Browser                         | Support IE Brower & Management Software Viewing |
| Mobile                          | WANAN App/IOS/Android                           |
| <b>Technical Specifications</b> |   |
| Temperature                     | -30°C ~ +60°C                                   |
| Humidity                        | 0% - 90%  |
| Protection                      | IK10, IP67                                      |
| Power                           | DC12V/POE(IEEE802.3af)                          |
| Consumption                     | < 2W  |
| Dimension                       | Ø 108 × 84 mm                                   |

## Dimensions

