

8MP(4K) 7*24 Full Colour POE Network Dome Camera



- 7*24 Full Colour Dome
- Fixed-focal (3.6mm)
- H.265/H.264
- 3840*2160 Mainstream resolution
- Support body detection & human frame

Specifications

| Model | OTRAFG804WHDC |
|--|--|
| Camera | |
| Image Sensor | 1/3" 8MP CMOS Sensor |
| Resolution | 8MP |
| Effective Pixels | 3840(H)*2160(V) |
| Lens | 3.6mm |
| Compression | H.265/H.264 |
| LUX | Color 0.05Lux@F1.2; B&W 0.005Lux@F1.2 |
| S/N | ≥50db(AGC OFF) |
| WDR | DWDR: >80db |
| Audio | |
| Audio/Intercom Input | Audio MIC Input (optional) |
| Audio Output | Built-in power magnify circuit |
| LED Type | CDS IR / Sensor Control / Warm LED / Extra add LED drive board (Optional) |
| Other Function | IRCU, Reset |
| Extension Function | Extension with IO |
| Network | |
| Main Stream | 2560*1440, 1-25fps/s 2304*1296、1920*1080、1280*720,1-30fps/s |
| Sub Stream | 704*576、640*480、640*360、352*288,1-30fps/s |
| Video Coding Compression | 128Kbps-8192bps Continuous Adjustable |
| Subtitle Overlay | Support Channel Name & Data & Time & Frame & Resolution & 4 Lines of Character Overlay |
| Camera Features | |
| Full Colour | Support |
| Data Transmission & Storage | |
| Data Record | Video & Picture |
| Storage Method | Cycling Recording & Alarm Recording |

| | |
|---------------------------------|---|
| Alarm Transfer | Brower & Management Software, App |
| Protocol | ONVIF |
| Browser | Support IE Brower & Management Software Viewing |
| Mobile | WANAN App/IOS/Android |
| Technical Specifications | |
| Temperature | -30°C ~ +60°C |
| Humidity | 0% - 90% |
| Power | DC12V/150mA |
| Dimensions | Φ 107 x 90(H) mm |
| Consumption | < 2W |

Dimensions

