

8MP(4K) IR IK10 IP67 POE Network Dome Camera



- IR POE Dome Camera
- Fixed-focal (2.8mm / 3.6mm)
- H.264/H.264+/H.265/H.265+
- 3840*2160 Mainstream resolution
- IK10, IP67

Specifications

Model	OTRAFG804WHDI
Camera	
Image Sensor	1/3" Progressive CMOS
Resolution	8MP
Effective Pixels	3840(H)*2160(V)
Lens	2.8mm / 3.6mm
Compression	H.264/H.264+/H.265/H.265+
LUX	Color 0.05Lux@F1.2; B&W 0.005Lux@F1.2
S/N	≥56db(AGC OFF)
WDR	120 dB
Illumination Distance	up to 30 m (98.43 ft) (IR LED)
Audio	
Audio/Intercom Input	Audio MIC Input (optional)
Audio Output	Built-in power magnify circuit
LED Type	CDS IR / Sensor Control / Warm LED / Extra add LED drive board (Optional)
Other Function	IRCUT, Reset
Extension Function	Extension with IO
Network	
Main Stream	2560*1440, 1-25fps/s 2304*1296、1920*1080、1280*720,1-30fps/s
Sub Stream	704*576、640*480、640*360、352*288,1-30fps/s
Video Coding Compression	128Kbps-8192bps Continuous Adjustable
Subtitle Overlay	Support Channel Name & Data & Time & Frame & Resolution & 4 Lines of Character Overlay
Data Transmission & Storage	
Data Record	Video & Picture
Storage Method	Cycling Recording & Alarm Recording
Alarm Transfer	Brower & Management Software, App

Protocol	ONVIF
Browser	Support IE Brower & Management Software Viewing
Mobile	WANAN App/IOS/Android
Technical Specifications	
Temperature	-30°C ~ +60°C
Humidity	0% - 90%
Protection	IK10, IP67
Power	DC12V/POE(IEEE802.3af)
Consumption	< 2W
Dimension	Ø 108 × 84 mm

Dimensions

